Package: mcmcderive (via r-universe)

October 27, 2026

Title Derive MCMC Parameters

Version 0.1.2.9008

Description Generates derived parameter(s) from Monte Carlo Markov Chain (MCMC) samples using R code. This allows Bayesian models to be fitted without the inclusion of derived parameters which add unnecessary clutter and slow model fitting. For more information on MCMC samples see Brooks et al. (2011) <isbn:978-1-4200-7941-8>.

License MIT + file LICENSE

URL https://github.com/poissonconsulting/mcmcderive, https://poissonconsulting.github.io/mcmcderive/

BugReports https://github.com/poissonconsulting/mcmcderive/issues

Imports abind, chk, extras, mcmcr, nlist, purrr, rlang, universals

Suggests coda, covr, doParallel, plyr, testthat (>= 3.0.0)

Config/Needs/website poissonconsulting/poissontemplate

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2.9000

Repository https://poissonconsulting.r-universe.dev

Date/Publication 2026-10-13 07:37:18 UTC

RemoteUrl https://github.com/poissonconsulting/mcmcderive

RemoteRef HEAD

RemoteSha e5c3b2a8f910cdb9a7220fff8e8a4c1564e05f92

Contents

expression_vectorize 2
mcmc_derive 3

Index **6**

`expression_vectorize` *Convert New Expression*

Description

Takes an expression and removes the for loop and adds `cbind` for arrays.

Usage

```
expression_vectorize(x)
```

Arguments

x	An expression

Value

An expression

Examples

```
expression_vectorize(rlang::expr(for (i in 1:nObs) {
  eCount[i] <- b0
}))
expression_vectorize(
  rlang::expr(
    for (i in 1:length(LogLength)) {
      eWeightLength[i] <- b0 + bDayte * Dayte[i]
    }
  )
)
expression_vectorize(
  rlang::expr(
    for (i in 1:nObs) {
      eAnnual[i] <- bAnn[Ann[i]] + bSA[Site[i], Ann[i]]
    }
  )
)
```

mcmc_derive *MCMC Derive*

Description

Generates an MCMC object with derived parameters from an MCMC object.

Usage

```
mcmc_derive(object, ...)

## S3 method for class 'nlist'
mcmc_derive(
  object,
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)

## S3 method for class 'nlists'
mcmc_derive(
  object,
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)

## S3 method for class 'mcmc'
mcmc_derive(
  object,
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)

## S3 method for class 'mcmc.list'
mcmc_derive(
  object,
```

```
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  parallel = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)

## S3 method for class 'mcmcr'
mcmc_derive(
  object,
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  parallel = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)

## S3 method for class 'mcmcrs'
mcmc_derive(
  object,
  expr,
  values = list(),
  monitor = ".*",
  primary = FALSE,
  parallel = FALSE,
  silent = getOption("mcmcderive.silent", FALSE),
  ...
)
```

Arguments

object	An MCMC object.
...	Unused.
expr	A string of the R code defining the values of the derived parameter(s) with respect to the parameters in object.
values	A named list of additional R objects to evaluate in the R expression.
monitor	A regular expression specifying the derived parameter(s) in expr to monitor.
primary	A flag specifying whether to include the original primary parameters in the new MCMC object.
silent	A flag specifying whether to suppress messages and warnings.
parallel	A flag specifying whether to generate the derived parameters for each chain in parallel.

Details

It's important to note that parameters in the expression that also occur in the original object are not included in the new object unless `primary = TRUE` in which case they are simply copied from the original object to the new one. This applies even when the primary parameters are redefined in values.

Value

An MCMC object with the derived parameter(s).

Methods (by class)

- `mcmc_derive(nlist)`: Get derived parameters for an `nlist::nlist-object()`
- `mcmc_derive(nlists)`: Get derived parameters for an `nlist::nlists-object()`
- `mcmc_derive(mcmc)`: Get derived parameters for an `coda::mcmc()` object
- `mcmc_derive(mcmc.list)`: Get derived parameters for an `coda::mcmc.list()` object
- `mcmc_derive(mcmcr)`: Get derived parameters for an `mcmcr::mcmcr-object()`
- `mcmc_derive(mcmcrs)`: Get derived parameters for an `mcmcr::mcmcrs-object()`

Examples

```
mcmcr::mcmcr_example

expr <- "
 log(alpha2) <- alpha
 gamma <- sum(alpha) * sigma"

mcmc_derive(mcmcr::mcmcr_example, expr, silent = TRUE)
```

Index

coda::mcmc(), *5*
coda::mcmc.list(), *5*

expression_vectorize, 2

mcmc_derive, 3